Danube east of Vienna Waterway Management in a National Park

26. April 2017



Danube East of Vienna

<complex-block>

Approx. 48 km long From: Freudenau Power Plant (River-km 1.921,0) To: Austrian-Slowak border (River-km 1.872,7) Height difference: approx. 18 m (40 cm/km) Fluctuations in water levels: up to 7 m

Deficits & objectives Danube East of Vienna



decoupling of river and floodplains, falling groundwater levels

→ Stabilization of water levels



habitats of typical local flora and fauna are at risk

→ Improvement of environmental conditions



limited competitiveness of inland waterway transport

→ Improvement of fairway conditions / opt. waterway infrastructure

High diversification of objectives interdisciplinary approach, stakeholder participation

Pilot projects east of Vienna



Pilot Project Bad Deutsch-Altenburg



© via donau I 6

viadonau

Integrative Monitoring Programme



Some Results

Results

- Granulometric riverbed stabilisation is technically feasible within strict quality requirements. It is now "state of the art".
- Overrun tests confirmed compatibility with navigation (propulsion).
- Contribution of coarser gravel to riverbed stability was over-estimated by numerical and physical models.
- Groynes have a significant influence on the river bed.
- New habitats establish after short periods of higher water levels and were populated nearly immediately.





- Dunes with height of max. 45 cm
- After dredging, dunes migrate by approx. 5,6 m/h in the dredging field
- Significant influence on riverbed stability & discussion of fairway depths

Integrated River Engineering Project

From large-scale project towards a catalogue of measures

- The results of the pilot phase have been combined with new developments in waterway management (WAMS) and traffic management (DoRIS Services).
- The implementation strategy was adopted to the findings: Turning away from a • large scale project ("General Project 2006") towards adopted maintenance processes and smaller optimization projects.
 - Catalogue of measures for the Danube East of Vienna
- Realization in order by priority
 - Priority 1: Realization by 2022 (Action Programme Danube of the MoT)
 - Priority 2: Realization by 2030

© via donau I 10

viadonau

Catalogue of Measures Optimization projects

management measures, etc.

Step-by-step approach in order by priority



Small-scale Measures

© via donau | 11

One big bottleneck? - dredging east of Vienna 2014-2016



Renaturation works Side arm reconnection and riverbank restoration



Catalogue of Measures Processes

Processes / Integrative Sediment Management

- opportunity for continuous improvement over the years.
- possibility to react on the effects of the work of previous years, on discharge, etc.

Types of processes

- Relocation of gravel (upstream)
 - gravel excavated in the course of maintenance dredging
 - gravel excavated in bedload traps
- Local addition of coarser gravel





© via donau I 14

Integrative Sediment Management

Maintenance section viadonau (Stream-km 1910,0 - 1872,7) Andlersdorf Straudorf Loimersdorf **Bed-load addition Verbund** Kopfstetter Prohistdor agram Eckartsau Witzelsdo HAINRURG 111 Bed load trap Treuschütt aintenance Regelsbrunn FI HAMEND Wildu Maria Ellend Addition of coarse gravel Klein-Neusiedl STERRE Enzersdorf **Bed-load relocation**

Discharge and loaded draught proactive and timely dredging of critical fords

Correlation between average loaded draught and discharge - Vienna dredging season starts 100% with the most critical 90% ford in August 80% Time of exceeding a certain water discharge Average loaded draught 70% 60% 50% 40% 30% 900 m3/s 20% •1300 m3/s 1800 m3/s 10% 12 Months Quelle: Hydrographisches Jahrbuch, via donau Durchschnittliche Abladetiefe: Relation Bratislava-Linz, EDDSG, Jahre 2007-2009 Überschreitungsdauer Auswertungszeitraum: 1980 - 2009, Tageswerte des Abflusses

bars: average loaded draught of vessels between Bratislava-Linz. EDDSG 2007-2009 lines: probability of exceeding 3 different water discharges between low and mean water (average over 30 years) [©]

© via donau I 16

viadonau

viadonau

Sediment management

Usage of dredged gravel east of Vienna 1996-2016







Added up gravel deficit 1996-2016 (profile distance 100 m)

viadonau



Integrated River Engineering Project / Catalogue of Measures

Supporting processes

- Scientific supervision / Monitoring to measure the impact of the measures and to ensure ongoing "Learning from the river" also in future.
- Continuation of **stakeholder participation** to integrate stakeholders from ecology and navigation and civil society.
 - Possibility to accompany and influence the implementation of the Catalogue of Measures.
 - Discussion on guiding principles for future management of the freeflowing section.

© via donau I 20

viadonau

Stakeholder Forum 2012-2015

The Stakeholder Forum ("Akteursforum") allowed the **structured integration of stakeholders** in the project. The forum ...

- accompanied the realization of the Pilot Project Bad Deutsch-Altenburg
- discussed the outcome and the consequences for future projects, especially the consequences for the Integrated River Engineering Project

Ten stakeholders with voting power:

- 4 stakeholders from economy / navigation sector
- 4 stakeholders from environmental NGOs
- 1 representative of National Park
- 1 representative of ICPDR

Observers were welcome to the meetings

The stakeholders were supported by an independent **Scientific Board**. It was made of 5 experts for the fields of navigation, ecological river engineering, hydrology and ground water, biodiversity, hydrobiology and fish ecology



Thank you for your attention!

Robert TÖGEL

Head of Team Integrated River Engineering Project T +43 50 4321-2612 robert.toegel@viadonau.org Donau-City-Straße 1, 1220 Vienna www.viadonau.org/fgp



The Integrated River Engineering Project and the Pilot Projects Bad-Deutsch Altenburg and Witzelsdorf were co-financed by the European Union within the Trans-European Transport Network (TEN-T) Programme