


# Good practices in suspended sediment monitoring: Continuous turbidity measurements

M. Haimann, Ph. Gmeiner, H. Habersack

 University of Natural Resources and Life Sciences,  
Vienna

## Spatial and temporal variability

- Suspended sediments vary in space and time




← Probe characteristic  $s_k = a s_s$   
Probe factor  $k_s = s_k / s_s$

← Cross-sectional characteristic  
 $s_m = a s_k$

← Discharge  $Q_s = s_m Q$

← Time  $V_s = \int_{t_1}^{t_2} Q_s(t) dt$





# Variability of suspended sediments

- Variation of suspended sediments with time




Figure 7.2 Variations of sediment yield over geological time. Based (A) on Tardy *et al.* (1989) and (B) on Degens *et al.* (1991)

(Walling, 1999)

## Temporal variability

- Often measured by instantaneous samples
- Many methods available to calculate suspended sediment loads based on these samples

# Temporal variability

## Interpolation methods

- Linear interpolation
- Averaging estimator

$$L = \sum_{m=1}^M \frac{C_m^{\text{int}} Q_m}{M} n$$

$$L = \frac{\sum_{i=1}^n A_i C_i}{\sum_{i=1}^n A_i} \frac{\sum_{i=1}^n A_i Q_i}{\sum_{i=1}^n A_i} n = \bar{C} \cdot \bar{Q} \cdot n$$

$$L = \frac{\sum_{i=1}^n A_i C_i}{\sum_{i=1}^n A_i} \frac{\sum_{i=1}^n Q_i}{n} n = \bar{C} \cdot \mu_q \cdot n$$

$$L = \frac{\sum_{i=1}^n A_i C_i Q_i}{\sum_{i=1}^n A_i} n = \overline{CQ} \cdot n$$

$$L = \frac{\frac{\sum_{i=1}^n A_i C_i Q_i}{\sum_{i=1}^n A_i}}{\frac{\sum_{i=1}^n Q_i}{n}} n = \overline{CQ} \frac{\mu_q}{\bar{Q}} n$$

Delmas M., Cerdan O., Cheviron B., Mouchel J. M. 2011, River basin sediment flux assessments. Hydrological Processes, 25, pp. 1587-1596.

Phillips J. M., Webb B. W., Walling D. E., Leeks G. J. L. 1999, Estimating the suspended sediment loads of rivers in the LOIS study area using infrequent samples. Hydrological Processes, 13, pp. 1035-1050.

Quilbé R., Rousseau A. N., Duchemin M., Poulin A., Gangbazo G., Villeneuve J.-P. 2006, Selecting a calculation method to estimate sediment and nutrient loads in streams: Application to the Beaurivage River (Québec, Canada). Journal of Hydrology, 326, pp. 295-310.


Walling D. E., Webb B. W. 1981, The reliability of suspended sediment load data. Erosion and Sediment Transport Measurement (Proceeding of the Florence Symposium, June 1981). IAHS Publ. no. 133., pp. 177-194.

Zamyadi A., Gallichand J., Duchemin M. 2007, Comparison of methods for estimating sediment and nitrogen loads from a small agricultural watershed. Canadian biosystems engineering, Vol. 49, pp. 1.27-1.36.

## Temporal variability

### Extrapolation methods

$$C = aQ^b$$



(Haimann et al., 2014)

Asselman N. E. M. 2000, Fitting and interpreting of sediment rating curves. Journal of Hydrology, 234, pp. 228-248.

Doomen A. M. C, Wijma E., Zwolsman J. J. G., Middelkoop H. 2008, Predicting suspended sediment concentrations in the Meuse River using a supply-based rating curve. Hydrological Processes, 22, pp. 1846-1856.

Horowitz A. J. 2003, An evaluation of sediment rating curves for estimating suspended sediment concentrations for subsequent flux calculations. Hydrological Processes, 17, pp. 3387-3409.



Walling D. E. 1977, Assessing the accuracy of suspended sediment rating curves for a small basin. Water resources research, Vol. 13, No. 3, pp. 531-538.

Walling D. E., Webb B. W. 1988, The reliability of rating curve estimates of suspended sediment yield: some further comments, Sediment Budgets (Proceeding of the Porto Alegre Symposium, December 1988), IAHS Publ. no. 174, pp. 337-350.

## Temporal variability

- Often measured by instantaneous samples
- Many methods available to calculate suspended sediment loads based on these samples
- Based on the applied method the results can differ substantially

## Temporal variability



(Haimann, 2015)



## Temporal variability

- Often measured by instantaneous samples
- Many methods available to calculate suspended sediment loads based on these samples
- Based on the applied method the results can differ substantially

## Temporal variability

- Often measured by instantaneous samples
- Many methods available to calculate suspended sediment loads based on these samples
- Based on the applied method the results can differ substantially
- No information on e.g. maximum concentration


## Surrogate technology

- Optical sensors

backscatter



transmission



S::can

- Acoustic sensors

Single frequency



(<https://www.sequoiasci.com>)

Multi frequency




SediScat™ Pro

(<http://www.hydrovision.de/>)

## Advantages of turbidity sensors

- Suspended sediment concentration correlates much better with turbidity than with water level / discharge



## Advantages of turbidity sensors

- Suspended sediment concentration correlates much better with turbidity than with water level / discharge
- Continuous information (e.g. 15 min interval)
- Easy to handle
- Can be connected to online monitoring system
- Turbidity sensors are comparatively cheap
- Optical sensors already used in many countries at the Danube River



## Disadvantages of turbidity sensors

- Turbidity sensors are not only dependent on concentration but also e.g. on the size of the reflecting particles --> have to be calibrated by water samples
- Point measurement only
- (Bio-) Fouling can occur




(Photo: HD Tirol)

(Photos: BMLFUW, 2008; 2017)

## Turbidity sensors

### What has to be considered when using turbidity sensors?

- Measurement range suitable for the river
- Cleaning system (e.g. wiper)



(<https://at.hach.com/>)




(Photo: viadonau)

## Turbidity sensors

### What has to be considered when using turbidity sensors?

- Measurement range suitable for the river
- Cleaning system (e.g. wiper)
- Installation height: varying with water level or fixed
- Enough water cover during low flow but not too close to the river bed



## Turbidity sensors

### What has to be considered when using turbidity sensors?


- Measurement range suitable for the river
- Cleaning system (e.g. wiper)
- Installation height: varying with water level or fixed
- Enough water cover during low flow but not too close to the river bed
- Retrieving the sensor should be possible at any water level for e.g. maintenance reason

## Installation of turbidity sensors



### Expeditionary measurements

### Cont. monitoring





## Installation of turbidity sensors



(Photo: HD Tirol)



(Photo: viadonau)



(Photo: viadonau)



(Photo: Verbund=



(Photo: Verbund)



(Photo: HD Oberösterreich)

## Calibration of turbidity sensors

### Why is calibration necessary?


- Turbidity sensors are not only dependent on concentration but also e.g. on the size of the reflecting particles
- Thus samples have to be taken close to the sensor to correct the data



Method	Frequency
Turbidity sensor	Continuously
Single point samples close to the sensor	High sediment discharge: min. daily Med. sediment discharge: min. 1-2 / week Low sediment discharge: rare

(BMLFUW, 2008; 2017)


## Data Processing



## Data processing

### Plausibility check


- Natural processes: e.g. heavy rainfall, flood event, snow melt
- Anthropogenic influences: e.g. dredging, construction works in the river
- Other influences: e.g. fouling, debris



Discharge (blue), turbidity data (red) and samples close to the sensor (black) (data source: viadonau)



## Data Processing






## Data processing

### How is the data calibrated?

- Two different methods are applied:
  - Statistical regression:



(Habersack et al., 2015)

## Data processing


### How is the data calibrated?

- Two different methods are applied:

- Statistical regression:


- Correction factor:

$$k_s = s_k / s_s$$



Turbidity sensor (red), samples (black), correction factor (blue)  
(data source: Hydrographic service Upper Austria)


## Calibration of turbidity sensors




Turbidity sensor (red), samples (black), suspended sediment concentration close to the sensor - linear regression (blue), suspended sediment concentration close to the sensor probe factor (green)

## Calibration of turbidity sensors

Continuous task as relation might change




## Data Processing






## Calibration of turbidity sensors



Discharge (blue), turbidity data (red), samples (black), concentration close to the sensor (green)  
(data source: viadonau)

## Data Processing



## Conclusions

- Continuous turbidity monitoring with OBS (or ABS) sensors mounted on the river bank
- If possible, automatized and connected to online monitoring system
- Calibration of sensors with samples taken close to the sensor

# Thank you for your attention!

**Marlene Haimann, Philipp Gmeiner, Helmut Habersack**  
**University of Natural Resources and Life Sciences**  
**Muthgasse 107**  
**1190 Vienna**

## References

- Bacher K. (2008): Schwebstoffmonitoring an der Drau. Diplomarbeit, Universität für Bodenkultur, Wien.
- Bittner G. (2008): Vergleich von Trübungssonden bei der Schwebstoffmessung unter definierten Laborbedingungen, Diplomarbeit, Universität für Bodenkultur, Wien.
- BMLFUW (2008; 2017): Schwebstoffe im Fließgewässer - Leitfaden zur Erfassung des Schwebstofftransports (Austrian Guideline of surveying suspended sediment transport) [https://www.bmnt.gv.at/wasser/wasser-oesterreich/wasserkreislauf/Schwebstoffe\\_LF.html](https://www.bmnt.gv.at/wasser/wasser-oesterreich/wasserkreislauf/Schwebstoffe_LF.html)
- Gmeiner Ph., Liedermann M., Haimann M., Tritthart M., Habersack H. (2016): Grundlegende Prozesse betreffend Hydraulik, Sedimenttransport und Flussmorphologie an der Donau. Österreichische Wasser- und Abfallwirtschaft, 68, 208-216; ISSN 0945-358X
- Habersack H., Gmeiner Ph., Haimann M., Hauer Ch., Holzapfel P., Klösch M., Liedermann M., Pessenlehner S., Tritthart M., Wagner B., Blamauer B., Glas M., Schober B. (2015): 2. Evaluation Report Christian-Doppler-Laboratory for Advanced Methods in River Monitoring, Modelling and Engineering, Vienna.
- Haimann M., Liedermann M., Lalk P., Habersack H. (2014): An integrated suspended sediment transport monitoring and analysis concept. Int J Sediment Res.; 29(2): 135-148.
- Haimann M. (2015): Heterogeneity in suspended sediment transport. Presentation. 2. Evaluation. Christian-Doppler-Laboratory for Advanced Methods in River Monitoring, Modelling and Engineering, Vienna.
- Hauer H. (2007): Schwebstoffmessung an der Messstelle Neumarkt/Raab. Diplomarbeit, Universität für Bodenkultur, Wien.
- Kerschbaumsteiner W. (2009): Schwebstoffmonitoring an österreichischen Fließgewässern unter Anwendung moderner Messtechnik. Dissertation. Universität für Bodenkultur, Wien.
- Lalk P., Haimann M., Habersack H. (2015): Application of a New Monitoring Strategy and Analysis Concept of Suspended Sediments in Austrian Rivers. In: Heininger, P., Cullmann, J. (Eds.), Sediment Matters, 247; Springer; ISBN 978-3-319-14695-9
- Walling D. (1999): Linking land use, erosion and sediment yields in river basins. Hydrobiologia 410: 223–240